©Gard Datasheet



» Basic Lock, left handing

CLIN-L

Basic Lock, left handing



When mounted on the front of the circuit breaker, this lock allows or prevents switching of the breaker.

- Special spindle sizes available on requestOptional available with locking lever
- Left handing operation

mGard range

mGard is the ultimate range of robust mechanical trapped key products. Trapped key technology offers purely mechanical access locks (removing the need for expensive wiring). mGard offers an extensive variety of modular interlocking solutions. Suitable for use in applications up to SIL3 (EN/IEC 62061), Category 4 and PLe (EN/ISO 13849-1), mGard is ideal for use in harsh environments and is tested to 1,000,000 operations.

Technical Specification

Lock construction	Zinc alloy with a durable satin-chrome finish to the lock casing. The internal lock components are made from stainless steel. Non drive spacers are made from PTFE. (CLSS locks have a full stainless steel lock casing)
Key	Stainless steel (purchased separately)

Article Codes	
Туре	Part N°
Breaker Lock, left handing	CLIN-L
Movement	Part N°
Clockwise Anti clockwise	C A
Degree of movement	Part N°
65	065
90	090
Spindle size	Part N°
9mm	09
22mm	22
Options	Part N°
Locking lever	F50037

Dimensional Drawing

