TECHNICAL DATA SHEET

BELLTRONIC **BANK UNIT DATA SHEET



PRODUCT DETAILS

The Belltronic Bank Men & Material unit is the same as the Standard Bank Unit except that it has an additional safety feature which will only allow 4/1, 4/2, 1, 2 and long ring to be transmitted when the unit on the station is in the material mode.

This prevents the station gates from being overridden and the conveyance being rung away at full speed.

The unit is manufactured in stainless steel and equipped with:

- A push button signalling device to communicate to the driver.
- Evolution or D-Tronic PC Board.
- Fitted with either a PP, Castell or Fortress key switch.
- Various audible devices, such as bell, sounder, cybertone, etc
- The unit is available in either 32V / 110V AC or 32V DC.
- This unit is fitted with a "Telltale" sounder.

Note: The unit has a switch-off facility feature and always completes every signal rung.

| Product Code: | Description: |
|---------------|--------------------------------------|
| *9504.98 | 15 Way, D-Tronic & Castell K/switch |
| *9504.44 | 15 Way, D-Tronic & PP K/switch |
| *9504.45 | 15 Way, Evolution & Castell K/switch |
| *9504.46 | 15 Way, Evolution & PP K/switch |

DIMENSIONAL DRAWING





