

PRO-LOCK

lockout tagout

LARGEST SELECTION OF LOCKOUT TAGOUT SAFETY PRODUCT AVAILABLE

ALUMINIUM & COMPOSITE
PADLOCKS

PADLOCK ENGRAVING AVAILABLE



Part No.	Specification	Description
ALP38S	Inner shackle:38mm; diameter:6mm	Support keyed differ, keyed alike, master keyed, and grand master keyed system.

ALUMINUM SAFETY PALDOCK

- $\ \, \bigcirc \,$ Aluminum body and triple–coated hardened chrome plated steel shackle.
- When unlocking the padlock, the shackle will pop up automatically.
- O Normal color: RED, YLW, BLU, ORG, GRN, PRP, BLK, SLV.
- Other shackle lengths can be customized.





SAFETY PADLOCK



Part No.	Shackle Material	A(mm)	B(mm)	C(mm)	Specification	
WCP38S	Steel	41	45	38	Support keyed alike, keyed differ, master keyed and grand master keyed system. *1key/lock	

- Made of copper cylinder and key. More resistantant to corrosion and rust. Very stable, with more then 1 million times operating.
- \odot Reinforced nylon body, withstand temperature from -20% to +120%. The steel shackle is chrome plated.
- O Key Retaining Feature: When the shackle is open, the key can't be removed.
- All different colors available.



SAFETY PADLOCK




Part No.	Description	Shackle Material	Specification
KA-P38P	Keyed Alike	Nylon	"P": Straight edge plastic
KD-P38P	Keyed Differ	INVIOIT	"P": Nylon shackle *1key/lock

- Reinforced nylon body, withstand temperature from -20℃ to +120℃. The steel shackle is chrome plated; the non-conductive shackle is made from nylon, withstand temperature from -20℃ to +120℃, ensuring the strength and deformation fracture not easily.
- O Key Retaining Feature: When the shackle is open, the key can't be removed.
- Laser printing and logo engraving available if required.
- All different colors available.



ADJUSTABLE BALL VALVE LOCKOUT



Part No.	Description
ABVL01	Suitable for pipes 1/2" to 2.5" in diameter, OPEN on pipes from 1/2" to 1.25"
ABVL02	Suitable for pipes 2" to 8" in diameter





- \odot Made from durable ABS, withstand temperature from $-20\,^{\circ}$ C to $+90\,^{\circ}$ C, highly resistant of cracking and abrasion and supports extreme weather temperature conditions.
- The two halves of the lockout encompass the ball valve handle to secure it from inadvertent activation of the valve handle.

ADJUSTABLE FLANGED BALL VALVE LOCKOUT

Part No.	Description
FBVL01	Suitable for 6.35mm(1/4") to 140mm(5") flanged ball valves

- O Accept up to 1 padlock, locking shackle max diameter 8mm.
- Available in red color, other colors can be customized, providing English tags.



ADJUSTABLE GATE VALVE LOCKOUT





- Made from durable ABS, withstand temperature from −20°C to +90°C.
- © Can be equipped together with padlocks. Padlock locking shackle max diameter 3/8"(9.8mm).
- Can be covered and rotated freely around valve wheel, and adjustable to fit a range of valve handles.


Part No.	Description	А	В	С
SGVL01	Suitable for valve handle 1" to 2 1/2" in diameter	80	30	20
SGVL02	Suitable for valve handle 2 1/2" to 5" in diameter	142	37	45
SGVL03	Suitable for valve handle 5" to 6 1/2" in diameter	184	44	63
SGVL04	Suitable for valve handle 6 1/2" to 10" in diameter	280	67	89
SGVL05	Suitable for valve handle 10" to 13" in diameter	364	67	105

- Made from durable ABS, withstand temperature from −20°C to +90°C. 0
- Once locked, it covers around the hand wheel and prevent the valve 0 wheel from being turned.
- Accept up to 1 padlock, locking shackle max diameter 9.8mm.
- 0 Available in 5 sizes and red color, other colors can be customized, providing English tag.

STANDARD GATE VALVE LOCKOUT













ADJUSTABLE STEEL CABLE LOCKOUT







CB01-4

CB01-6


- Cock body: made of ABS, withstands chemicals.
- O Cable: tough, flexible multi-stranded steel cable, with clear plastic Includes high-visibility, re-usable, write-on safety labels. Can be insulation coating.
- O Cable length can be customized.
- Accepts up to 4 padlocks for multiple lockout application.






- customized.
- O Ideal for locking out a single valve or multiple side-by-side valves.

ADJUSTABLE STEEL CABLE LOCKOUT














- Made from industrial durable nylon, and insulation coated steel cable.
- Designed to effectively lock out a variety of isolation points, including gate valves, "T" valve handles and other hard-to-secure mechanical devices.
- The handle is designed to operate the device without any tools needed.
- Cable length and color can be customized.
- Accepts up to 8 padlocks for multiple lockout application.

Part No.	Material	Description
CS01-2.5S-256	Aluminum alloy body, with galvanized cable	Cable diameter 2.5mm, length 256mm
CS01-2.5S-1000	Aluminum alloy body, with galvanized cable	Cable diameter 2.5mm, length 1000mm
CS02-1.8S-256	ABS body, with steel cable	Cable diameter 1.8mm, length 256mm
CS02-1.8P-256	ABS body ,with insulation coated steel cable	Cable diameter 1.8mm, length 256mm

- Ideal for long term uses, each car seal is self locking. The only way to remove it is by cutting after the cable passed through the body.
- $\ \ \bigcirc$ All car seals can be laser printed with individually numbering.
- The length of the cable can be customized.
- O Colors can be customized, normally in red, yellow, green and blue.

SECURITY SEAL LOCKOUT



CS01-2.5S-256/1000

CS02-1.8S-256

CS02-1.8P-256

MINIATURE CIRCUIT BREAKER LOCKOUT

Part No.	Description
TBLO	TBLO (Tie Bar Lockout), no hole in breakers required









- Made from engineering plastic strengthened nylon PA.
- Applied for most existing types of European and Asian circuitbreakers.
- Suggest to be equipped together with a padlock.
- Easily installed, no tools needed.
- O Can take a padlock with shackle diameter up to 9/32"(7mm).
- O Available for multi-pole breakers.

CIRCUIT BREAKI	ER LOCKOUT	Part No.	Description	
Φ9mm CBL02-1	Ф ^{9mm} CBL02-2	CBL02-1	lock hole:9mm, max clamping 10.5mm, need a small screw driver to install.	
		CBL02-2	lock hole:9mm, max clamping 10.5mm, without installing tools needed.	
		CBL02-3	lock hole:10mm, max clamping 10.5mm, without installing tools needed.	
10.5mm				
Ф 10mm	10.5mm			
10.5mm CBL0	2–3			

- $\ \, \bigcirc \,$ Made from engineering plastic strengthened nylon PA.
- O Lock out different types of circuit breakers.

CLAMP-ON CIRCUIT BREAKER LOCKOUT

Part No. CBL11 For 120–277V breaker lockouts, handle width ≤16.5mm







- Made of rugged polypropylene and impact modified nylon.
- sliding switches and switches with large angular rotation.
- O Can be easily operated without any tools.

Part No.		Description	CIRCUIT BREAKER	LOCKOUT
CBL11-2	Dedicated to Schneider circuit breakers EZD below 100A			
CBL11-3	Dedicated to Schneider cir	cuit breaker EZD between 160~250A		
		CANCEL STATE OF THE PROPERTY O	CBL11-3	CBL11-2

- ◎Made of rugged polypropylene and impact modified nylon, temperature resistance -5° C to $+100^{\circ}$ C.
- ©Can be easily operated without any tools.

O Accepts lock shackles up to 9/32" (7.5mm)in diameter.

CLAMP-ON CIRCUIT BREAKER LOCKOUT

Part No.	Description
CBL12	For 480–600V breaker lockouts, handle width ≤41mm







- Made of rugged polypropylene and impact modified nylon.
- © Can be used with lockout cleats in the bottom for hard locking long © Accepts lock shackles up to 9/32" (7.5mm) in diameter. sliding switches and switches with large angular rotation.
- O Can be easily operated without any tools.

MULTI-FUNCTIONAL CIRCUIT BREAKER LOCKOUT

Part No.	Description
CBL41	Suitable for locking out multi–pole breakers and works with most tie–bar toggles









- Made from engineering plastic strengthened nylon PA,temperature
 Comes with a locking screw, you can easily lock without using other resistance -20°C to $+120^{\circ}\text{C}$.
- O Compact size allows for locking out adjacent breakers.
- locking tools. Slotting allows screwdriver adjustment.
- O Can take a padlock with shackle diameter up to 8.5mm.

ELECTRICAL PLUG LOCKOUT




Part No.	Description	А	В	С	d1
EPL04	Suitable for plugs≤58mm in size	110	70	21	7
EPL05	Suitable for plugs≤78mm in size	190	90	25	7

- \odot Made of ABS engineering plastic, Temperature resistance $-20\,^{\circ}\!\!\mathrm{C}$ to $+90\,^{\circ}\!\!\mathrm{C}$.
- O Can be managed by 2 person at the same time.
- O Suitable for industrial and domestic plug locking.



CYLINDER TANK LOCKOUT








Part No.	А	В	С	D
ASL03	92	40	33	45
ASL03-2	83	37	/	31



- Made from durable ABS.
- spark proof and chemical resistance.
- Resistant to cracking and abrasion extreme weather and temperature conditons.
- OCan be equipped together with hasps and padlocks.


STEEL LOCKOUT HASP



Part No.	Description
SH01	Jaw Size 1"(25mm), accept up to 6 padlocks.
SH02	Jaw Size 1.5"(38mm), accept up to 6 padlocks.

- Mandle is made from PA and lock shackle is made from chrome plated steel with red plastic or vinyl coated body, rust proof.
- Allow multiple padlocks to be used when isolating one energy source.
- O Lock holes: 9.5mm in diameter.
- O Jaw size: 1"(25mm) & 1.5"(38mm).

NYLON LOCKOUT HASP



Part No		Description
NH01	Overall size	e: 44 × 175mm, accept up to 6 padlocks.

- Made from durable nylon.
- Non-conductive body, applied to electric power isolation with high requirements on corrosive and explosion-proof places.
- Allow multiple padlocks to be used when isolating one energy source.
- Labels can be customized.

SAFETY WARNING TAG

- Made from PVC material.
- The tag indicates who is responsible for placing the lockout device and who is authorized to remove it or make changes to it.
- O Can be written by erasable pen for repeated using.
- Other wording and design can be custom made.

Part No.	Description
LT02	75mm(W) × 146mm(H) × 0.5mm(T)



SAFETY WARNING TAG

- Made from PVC material.
- The tag indicates who is responsible for placing the lockout device and who is authorized to remove it or make changes to it.
- O Can be written by erasable pen for repeated using.
- Other wording and design can be custom made.

Part No.	Description
LT01	$75\text{mm}(W)\times146\text{mm}(H)\times0.5\text{mm}(T)$
LT03	75 mm(W) \times 146 mm(H) \times 0.5 mm(T)







Description

Size: 310mm × 92mm, hole diameter: 60mm, 1 tag with 1 holder.

LT01 LT03

SCAFFOLD HOLDER TAG





SLT01 SLT01-T

Made from ABS.

Part No.

SLT01

- Provides systematic, procedural and legal compliance for scaffolds on work sites.
- Provides a clear inspection trail giving integrity and control of work carried out.
- The tags are available in three durable write-on materials, providing highly visual and eye-catching information.
- Each with a scaffold tag holder and a tag. The tags can be customized.

PORTABLE GROUP LOCK BOX

- Made from surface high temperature spraying plastic treatment steel plate and stainless steel nylon handle.
- Several people can lock the important parts at the same time.
- Can be used as mini portable lockout box, can accommodate several tagout, hasp, mini lockout etc.
- The label message in English. Other langue can be custom made.

Part No.	Description
LK01	Size: $227mm(W) \times 152mm(H) \times 88mm(D)$, can accommodate $12padlocks$.



Part No.	Description
LK03	$360\text{mm}(W) \times 450\text{mm}(H) \times 163\text{mm}(D)$

- Made from surface high temperature spraying plastic treatment steel plate.
- There are two adjustable separators which can allocate spaces easily.
- The station is multifunctional for all kinds of lockouts, especially for departmental usage.
- O Can be customized made non-perspective panel.
- Any size station can be customized.

MANAGEMENT LOCKOUT STATION






Part No.	Description
LK21	165 mm(W) $\times 325$ mm(H) $\times 85$ mm(D)

- Made from surface high temperature spraying plastic treatment steel plate and stainless steel and nylon handle.
- O Device design for key store when large scale equipment shut down.
- Can be used as mini portable lockout box, can accommodate several tagout, hasps, mini lockout etc.
- O Double function: wall mounting type or portable.
- Integrated store space can accommodate 12 padlocks orderly or hundreds of keys scatteredly.
- O Up to 14 workers can lock it at the same time.
- Other colors can be customized.

GROUP LOCKOUT BOX



Part No.	Description	
LS01	$410\text{mm(W)} \times 315\text{mm(H)} \times 65\text{mm(D)}$	
LS02	565 mm(W) $\times 400$ mm(H) $\times 65$ mm(D)	
LS03	565 mm(W) \times 400 mm(H) \times 65 mm(D), with holder for small lockout devices.	

- Made from engineering plastic PC.
- One piece design, with a cover to lock out.
- O Can accommodate padlocks, hasps, lockout tags and some ties.
- There's a lockable combination padlock hole for locking out as a limit access to unauthorized employees.

LOCKOUT STATION







Part No.	Description	
Ls32	Can accommodate 40 padlocks, 4 hasps and tags.	

- © The lockout station is made of engineering plastic ABS with transparent PC cover.
- The pc cover protects the inside lockouts from dust and missing. It can accommodate padlocks, hasps, lockout tags and some other
- O lockout devices.

There is an overall padlock hole to lock out the station and preventing the

- © stored lockouts inside from unauthorized employees.
- $^{\odot}$ The overall size: 603mm(W) \times 600mm(H) \times 66.8mm(D).

LOCKOUT STATION



LS32

Part No.	Products	Description	Part No.	Products	Description
LG03	Section Krist	Lockout kit Box (PLK11) × 1; Lockout Hasp (SH01) × 2; Lockout Hasp (SH02) × 2; Safety Padlock (P38S–RED) × 4; Lockout Hasp (NH01) × 2; Cable Lockout (CB01–6) × 1; Valve Lockout (AGVL01) × 1; Valve Lockout (ABVL01) × 1; Breaker Lockout (CBL11) × 2; Breaker Lockout (CBL12) × 1; Breaker Lockout (TBLO) × 2; Lockout Tag (LT03) × 12.	LG41	Lockout	Lockout bag (LB41) 1PC; Safety padlock (P38S–RED) × 1 Safety padlock (PC175–RED) × 1; Lockout tag (LT03) × 12; Breaker lockout (CBL32) × 2; Breaker lockout (CBL31) × 1; Lockout hasp (SH01) × 1;





011 873 4332



JOHANNESBURG

10 Fobian Street, Hughes Boksburg, 1459

sales@deebar.co.za

NORTH WEST

25 Neethling Street Stilfontein 2551

northwest@deebar.co.za

RUSTENBURG

11 ACBO Industrial Park Rustenburg 0299

rust@deebar.co.za

Scan Our QR Code To Read About Our



