**©Gard** Datasheet



» Single Door Interlock

DM1



## Single Door Interlock

- No product handing issues:
- 4 head rotation angles with an adjustment of 360° at 90° increments with +/-5° fine adjustment Two actuator entry points
- All DM locks have stainless steel heads
- Tamper resistant head mechanism
- · Choice of actuator

## mGard range

mGard is the ultimate range of robust mechanical trapped key products. Trapped key technology offers purely mechanical access locks (removing the need for expensive wiring). mGard offers an extensive variety of modular interlocking solutions. Suitable for use in applications up to SIL3 (EN/IEC 62061), Category 4 and PLe (EN/ISO 13849-1), mGard is ideal for use in harsh environments and is tested to 1,000,000 operations.

## **Technical Specification**

**Dimensional Drawing** 

22

Housing Materials Body DM	Die-cast zinc body with pearl bronze plated finish
Housing Materials Body DMS	Full stainless steel
Head	Full stainless steel
Internals	Full stainless steel
Lock Mechanism DM	CL or ML lock types are of die-cast zinc
	body with stainless operating mechanism
Lock Mechanism DMS	CLS or MLS lock types are full stainless
	steel
Key	Stainless steel (purchased separately)

44.5	Ø34.9
------	-------

## **Article Codes** N° of Locks Part Nº 1 DM1 Nº of Locks (Full Stainless Steel) Part Nº 1 DMS1

Lock Type

Key and lock types must be specified seperatly

Actuator Type

Actuator type must be specified seperatly

64.25

